



PECORA CORPORATION
Architectural Weatherproofing Products
U.S.A. • since 1862

ARCHITECTURAL URETHANE SEALANTS

Dynatrol™ II
(2-pt urethane)

Dynaflex™
(2-pt urethane)

Dynatred™
(2-pt urethane)

STANDARD URETHANE COLORS

Custom colors available upon request

Dynatrol™ II, Dynaflex™, Dynatred™, Dynapoxy™:

Minimum Order Quantities for Non-Standard Colors:
5 Color Packs

Color Packs for Standard and Non-Standard Colors are sold in 5 unit increments.

This guide offers a representation of color; when matching is critical, a cured or applied color sample is highly recommended.

Pecora Corporation

165 Wambold Rd
Harleysville, PA 19438
Phone: (215) 723-6051
(800) 523-6688
Fax: (215) 721-0286

www.pecora.com

An ISO-9001:2000 certified company.

Brite White	CF26	Tan	545
Tru-White	345	Buff	512
Off-White	516	Colonial Tan	CF13
Dover Sky	CF14	Mocha Cream	CF34
Brushed Pewter	CF42	Toasted Almond	CF54
Anodized Aluminum	804	Natural Stone	565
Aluminum Stone	515	Desert Tan	530
London Fog	CF44	Adobe Accent	CF10
Stone Grey	CF53	Redwood Tan	CF43
Dark Grey	048	Brick Red	CF16
Limestone	039	Tile Red	CF22
Putty Grey	CF20	Red Rock	955
Pearl Ash	CF11	River Rouge	CF37
Van Dyke	CF18	Sierra Tan	CF47
Natural White	CF33	Rose	CF05
Sandstone	951	Texas Pink	CF48
Desert Sun	CF41	Smoky Brown	CF45
Eggshell Cream	CF04	Bronze	314
Manor White	CF08	Charcoal Gray	950
Precast	113	Chocolate	CF49
Amarillo White	CF02	Classic Bronze	046
Almond	792	Granite Grey	CF30
Beige	595	Black	012
Prairie Clay	CF07	Patriot Blue	CF01
Sandalwood Beige	CF09	Evergreen	CF03
Beige Grey	525		

NOTE: All 51 colors available for use with Dynapoxy™.

STANDARD URETHANE COLORS

Custom colors available upon request

Dynatrol™ I-XL, Dynaflex™ SC:
Minimum Order Quantities for **Non-Standard Colors:**
200 Gallons

Dynatrol™ I-XL (1-pt urethane)

White	336
Anodized Aluminum	804
Aluminum Stone	515
Limestone	039
Beige	595
Tan	545
Classic Bronze	046
Black	012

Pecora® Security System

Dynaflex™ SC (silyl terminated polyurethane(STPU))

Tru-White	345
Limestone	039

Dynapoxy™ EP-1200 (2-pt epoxy)

Dynatrol™ II (2-pt urethane)

Dynaflex™ (2-pt urethane)

Dynapoxy™, Dynatrol™ II, and Dynaflex™ colors are available in the 51 standard colors on the other side of this card in addition to virtually any non-standard color.

This guide offers a representation of color; when matching is critical, a cured or applied color sample is highly recommended.

Pecora Corporation
165 Wambold Rd
Harleysville, PA 19438
Phone: (215) 723-6051
(800) 523-6688
Fax: (215) 721-0286

www.pecora.com
An ISO-9001:2000 certified company.

COVERAGE CHART (231 cu. in./gal.)

Joint Depth (in.) x Width (in.)	Linear feet per Gal.	Joint Depth (in.) x Width (in.)	Linear feet per Gal.
1/8 x 1/8	1232.0	3/8 x 7/8	58.7
1/8 x 1/4	616.0	3/8 x 1	51.3
1/8 x 3/8	410.7		
1/8 x 1/2	308.0	1/2 x 1/2	77.0
1/8 x 5/8	246.4	1/2 x 5/8	61.6
1/8 x 3/4	205.3	1/2 x 3/4	51.3
1/8 x 7/8	176.0	1/2 x 7/8	44.0
1/8 x 1	154.0	1/2 x 1	38.5
1/4 x 1/4	308.0	5/8 x 5/8	49.3
1/4 x 3/8	205.0	5/8 x 3/4	41.1
1/4 x 1/2	154.0	5/8 x 7/8	35.2
1/4 x 5/8	123.2	5/8 x 1	30.8
1/4 x 3/4	102.7		
1/4 x 7/8	88.0	3/4 x 3/4	34.2
1/4 x 1	77.0	3/4 x 7/8	29.3
		3/4 x 1	25.7
3/8 x 3/8	136.9		
3/8 x 1/2	102.7	7/8 x 7/8	25.1
3/8 x 5/8	82.1	7/8 x 1	22.0
3/8 x 3/4	68.4	1 x 1	19.3

Joint Depth (in.) x Width (in.) x Length (in.) x 0.053 = gallons required

PEC191 3/15